


Datasheet Conveyor Belt

Berenkoog 25
1822 BH Alkmaar
The Netherlands

T: +31 (0)72 562 22 34
F: +31 (0)72 561 32 38

E: sales@nitta.nl
www.nittacorporation.com

- **NITTA BELT TYPE:**
2 XRAFP 15/V/T SC
- **Nitta Japan code:**



Construction: 2 plies polyester, extremely rigid, antistatic

	TOP COVER	INNER LAYER	BOTTOM SIDE
Material:	PU	PVC	Impregnated antistatic fabric
Thickness:	1,5		0,1 mm (approx.)
Colour:	Transparent	White	Transparent
Hardness:	92 Shore A		90 Shore A
Profile:	-		-

Total thickness:	3,7	mm (approx.)
Weight:	4,3	kg/m² (approx.)
Max. width:	3100	mm
Belt support:	Sliderbed (Rollers), Flat	

Rating at 1% elongation:	9	N/mm
Advised pretension:	4 - 7	N/mm
Maximum allowable tension:	16	N/mm
Temperature range:	-10 to +80	°C

Minimum pulley diameters:		
Flexing:	100	mm
Backflexing:	150	mm

Special approval: Not applicable

Applications:

- For applications in the tile and brick industry
- Excellent wear and cut resistance
- Oil and grease resistant
- Steel industry for transport of sheetmetal